


IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Sub B1 ✓
A
Claim 1 (original): A pilot nozzle for a gas turbine combustor comprising:
a fuel oil supply pipe passed through a cylinder unit provided in an axial direction of the pilot nozzle;
a heat-shielding air layer formed between the fuel oil supply pipe and the cylinder unit; and
a plurality of atomized-fluid supply paths provided in a circumferential direction of the cylinder unit.


○ Claim 2 (currently amended): The pilot nozzle according to claim 1, wherein the fuel oil supply pipe ~~has a portion at a predetermined distance from the front end fixed to the cylinder unit, and~~ has a rear end portion for supplying the fuel therefrom held by a structure so as not to be restricted to an restrict a displacement in axial direction due to thermal expansion or compression.

○ Claim 3 (currently amended): The pilot nozzle according to claim 2, further comprising:
a plurality of fuel gas supply paths provided in a circumferential direction of the cylinder unit;
a front end portion connected to an end portion of the cylinder unit; and
a distribution section disposed between the cylinder unit and the front end portion,
wherein the fuel gas supply paths and the atomized-fluid supply paths are disposed alternately in the circumferential direction respectively within the cylinder unit, the front end portion is provided with an atomized-fluid flow path and a fuel gas flow path which is

 disposed outside the atomized-fluid flow path, and the distributing section connects the fuel gas supply paths with the fuel gas flow path and the atomized-fluid supply paths with the atomized-fluid flow path respectively, wherein the distributing section is a cylindrical structure disposed inside the cylindrical space front end portion, and has a supply path converter which having a hollow inside the structure, has a hole A provided at a center portion of the end surface at one end through which the fuel oil supply pipe is connected to a fuel supply path, and has a first converting flow path hole B communicated to through which the atomized-fluid supply paths are converted to the atomized-fluid flow path having a ring-shaped cross-section, inside of the cylindrical structure and a second converting flow path [[G]] through which the fuel gas supply paths are converted to the fuel gas flow path having a ring-shaped cross-section communicated to the outside of the cylindrical structure, formed respectively at the outside of the end surface in a radial direction of the hole A, with the fuel oil supply pipe having substantially the same diameter as the hole A passed through the hole A, the atomized fluid supply path connected to the hole B, and the flow path C connected to the fuel gas supply path.

✓ Claim 4 (original): A pilot nozzle for a gas turbine combustor comprising:
a fuel oil supply pipe passed through a cylinder unit provided in an axial direction of the pilot nozzle;
a heat-shielding air layer formed between the fuel oil supply pipe and the cylinder unit; and
a plurality of atomized-fluid supply paths and fuel gas supply paths provided in a circumferential direction of the cylinder unit.

◇ Claim 5 (currently amended): The pilot nozzle according to claim 4, further comprising:

 a front end portion connected to an end portion of the cylinder unit; and
a distributing section disposed between the cylinder unit and the front end portion,
wherein the fuel gas supply paths and the atomized-fluid supply paths are disposed alternately and uniformly in the circumferential direction respectively within the cylinder unit, a portion near a the front end portion is provided with an atomized-fluid flow path and a fuel gas flow path which is disposed outside the atomized-fluid flow path of the pilot nozzle ~~has a structure having concentrically superimposed in multiple layers, and [[a]] the~~
distributing section connects the fuel gas supply paths with the fuel gas flow path and the atomized-fluid supply paths with the atomized-fluid flow path ~~to paths between separate cylinders respectively.~~

④ Claim 6 (currently amended): The pilot nozzle according to claim 4, wherein the fuel oil supply pipe ~~has a portion at a predetermined distance from the front end fixed to the cylinder unit, and~~ has a rear end portion for supplying the fuel therefrom held by a structure ~~so as not to restrict a displacement be restricted to an in axial direction~~ due to thermal expansion or compression.

○ Claim 7 (currently amended): The pilot nozzle according to claim 5, wherein the distributing section is ~~a cylindrical structure~~ disposed inside the front end portion, cylindrical space and has a supply path converter which having a hollow inside structure, has a hole ~~[[A]] provided at a center portion of the end surface at one end, through which the fuel oil supply pipe is connected to a fuel supply path, and has a first converting flow path hole B communicated to~~ through which the atomized-fluid supply paths are converted to the atomized-fluid flow path having a ring-shaped cross-section, inside of the cylindrical structure and a second converting flow path ~~[[C]] through which the fuel gas supply paths are converted to the fuel gas flow path having a ring-shaped cross-section communicated to the~~

~~outside of the cylindrical structure, formed respectively at the outside of the end surface in a radial direction of the hole A, with the fuel oil supply pipe having substantially the same diameter as the hole A passed through the hole A, the atomized fluid supply path connected to the hole B, and the flow path C connected to the fuel gas supply path.~~

○ Claim 8 (currently amended): The pilot nozzle according to claim 6, further comprising:

a front end portion connected to an end portion of the cylinder unit; and
a distributing section disposed between the cylinder unit and the front end portion,
wherein the fuel gas supply paths and the atomized-fluid supply paths are disposed alternately and uniformly in the circumferential direction respectively within the cylinder unit, the front end portion is provided with an atomized-fluid flow path and a fuel gas flow path which is disposed outside the atomized-fluid flow path, and the distributing section connects the fuel gas supply paths with the fuel gas flow path and the atomized-fluid supply paths with the atomized-fluid flow path respectively,

wherein the distributing section is a cylindrical structure disposed inside the front end portion, cylindrical space and has a supply path converter which having a hollow inside the structure, has a hole A provided at a center portion of the end surface at one end, through which the fuel oil supply pipe is connected to a fuel supply path, and has a first converting flow path hole B communicated to through which the atomized-fluid supply paths are converted to the atomized-fluid flow path having a ring-shaped cross-section, inside of the cylindrical structure and a second converting flow path [[C]] through which the fuel gas supply paths are converted to the fuel gas flow path having a ring-shaped cross-section communicated to the outside of the cylindrical structure, formed respectively at the outside of the end surface in a radial direction of the hole A, with the fuel oil supply pipe having

substantially the same diameter as the hole A passed through the hole A, the atomized fluid supply path connected to the hole B, and the flow path C connected to the fuel gas supply path.

Claim 9 (currently amended): A supply path converter comprising:

a cylinder having an end surface at one end and that is a cylindrical structure disposed inside the a cylindrical space and having a hollow inside the structure,

wherein the cylinder is provided with ^A [[has]] a hole A provided at a center portion of the end surface for passing a fuel supply path therethrough at one end, and has a first
^B converting flow path having an opening adjacent to the hole and communicating hole B
^A communicated to the hollow for converting into a first supply path connected to the hollow
inside the cylinder and having a ring-shaped cross-section, inside of the cylindrical structure
and a ^C second converting flow path having an opening adjacent to the hole and communicating
C communicated to the outside of the cylinder for converting into a second supply path
formed outside the cylinder ~~cylindrical structure, formed respectively at the outside of the end~~
~~surface in a radial direction of the hole A, with a pipe having substantially the same diameter~~
~~as the hole A passed through the hole A, and the hole B and the flow path C connected with~~
~~supply paths disposed in a circumferential direction of the same end surface respectively.~~